Mobile platform with deployable ring for bus roof access



Design and manufacture of a **mobile height-adjustable platform with deployable ring protection**. This solution provides easy access to vehicle roofs, with enhanced safety thanks to fixed and sliding guardrails that adapt perfectly to the contours of buses.



Reliability and durability

- Robust extruded aluminum structure: high corrosion resistance, maintenance-free.
- Galvanized steel frame for maximum durability.

Secure access to the work area

- Deployable ring protection on the roof with sliding lower sections on three sides, ensuring. complete enclosure and full fall protection at height.
- Peripheral guardrails on the platform (handrail, intermediate rail, baseboard).
- Secure staircase with anti-slip ribbed aluminum steps, handrails, and a top safety gate.



Mobile platform with deployable ring for bus roof access

"Safety is of paramount importance to us at ANDERSON TRAVEL. Once we saw a demonstration of the FORTAL Platform and how staff can easily and safely use it to access all areas of the roof of our motor coaches we were impressed.

All our air conditioning units and the solar panels fitted on a number of vehicles, are situated on the roofs of our vehicles so to have that peace of mind that our staff are safe and secure when working at height is great news.

As a company FORTAL were wonderful to deal with, assisting us through the whole process from the initial demonstration through the ordering process, regular updates on build progress, and the delivery was on time and seamless.

A great company to work with! "



ANDERSON - Director
ANDERSON TRAVEL company
(UNITED KINGDOM)





Comfort and ergonomics

- Height-adjustable platform: 2700 to 3700 mm.
- Variable-angle staircase: 35° to 55°, adaptable to intervention height.
- Spacious working area once the ring is deployed: 5000 x 2250 mm.
- Anti-slip aluminum flat sheet coating (4.4 mm thick, platform dimensions: 5000 x 1540 mm).

Mobility and easy handling

- Easy to move with 4 double swivel wheels Ø200 mm with brakes.
- Wheels retractable via crank jacks for working position.
- In use, the platform rests on stabilizing pads, ensuring optimal stability.
- Non-marking rubber protection on the vehicle side to prevent impact.

